

# Data Sheet

## Fairfield Series

### of Solid Vinyl Siding



For a Lifetime of Home Beauty


Illustration	Description/Packaging	Colors/Color Nos.	* Premium colors are made with Armor Coat UVA™
	<b>Double 4"</b> Length 12' 6" 24 Panels/Carton 2 Sq./Carton Carton Weight: 89.80 lbs.	White Birch (02) Classic Sand (11) Warm Sandalwood (17) Sunny Maize (22) Summer Wheat (26)	Autumn Taupe (28) Dove Gray (40) Harbor Stone (44) *Vintage Sage (55) *Adobe Clay (60)
			*Soft Heather (63) *Wicker Beige (65) *Terra Clay (69) *Victorian Slate (67)


Illustration	Description/Packaging	Colors/Color Nos.	* Premium colors are made with Armor Coat UVA™
	<b>Double 5"</b> Length 12' 20 Panels/Carton 2 Sq./Carton Carton Weight: 82.40 lbs.	White Birch (02) Classic Sand (11) Warm Sandalwood (17) Sunny Maize (22) Summer Wheat (26)	Autumn Taupe (28) Dove Gray (40) Harbor Stone (44) *Vintage Sage (55) *Adobe Clay (60)
			*Soft Heather (63) *Wicker Beige (65) *Terra Clay (69) *Victorian Slate (67)



Illustration	Description/Packaging	Colors/Color Nos.	* Premium colors are made with Armor Coat UVA™
	<b>4" Dutchlap</b> Length 12' 6" 24 Panels/Carton 2 Sq./Carton Carton Weight: 92.70 lbs.	White Birch (02) Classic Sand (11) Warm Sandalwood (17) Sunny Maize (22) Summer Wheat (26)	Autumn Taupe (28) Dove Gray (40) Harbor Stone (44) *Vintage Sage (55) *Adobe Clay (60)
			*Soft Heather (63) *Wicker Beige (65) *Terra Clay (69) *Victorian Slate (67)

Illustration	Description/Packaging	Colors/Color Nos.	* Premium colors are made with Armor Coat UVA™
	<b>5" Dutchlap</b> Length 12' 20 Panels/Carton 2 Sq./Carton Carton Weight: 83.10 lbs.	White Birch (02) Classic Sand (11) Warm Sandalwood (17) Sunny Maize (22) Summer Wheat (26)	Autumn Taupe (28) Dove Gray (40) Harbor Stone (44) *Vintage Sage (55) *Adobe Clay (60)
			*Soft Heather (63) *Wicker Beige (65) *Terra Clay (69) *Victorian Slate (67)

## Fairfield Series Solid Vinyl Siding

*Styles to fit your most exacting need.*

### Product Test Data

Siding Thickness.....	.044" ± .001"
Specific Gravity.....	1.45
Tensile Strength (PSI).....	7,154
Tensile Modulus (PSI).....	416,900
IZOD Impact Strength @ 32°F.....	Passes per ASTM D3679
Heat Deflection Temp. @ 264 PSI.....	169°F
Coefficient of Linear Expansion.....	3.30 x 10 <sup>-5</sup>
Weight.....	44 lbs. per square
Warpage.....	0.00"
Heat Shrinkage.....	0.3%



Style Crest, Inc.  
2450 Enterprise Street  
Drawer A  
Fremont, OH 43420

Impact Resistance.....	Passes per ASTM D3679
Surface Distortion @ 140°F.....	0
Flame Spread Index.....	10
Fire Rating.....	Class A
Smoke Developed.....	395
Fuel Contribution.....	0
Average Time Of Burning.....	Self extinguished
Average Extent Of Burning.....	2.379mm
Weathering.....	Passes per ASTM D3679
Windload Rating*.....	193 MPH

\*(Wind Velocity based on IBC)

*Fairfield Vinyl Siding passes or exceeds all industry standards per ASTM D3679.*

Made in the U.S.A. by America's dedicated workforce.

Specifications subject to change without notice.

