

HIGH PERFORMANCE SPECIALTY POLYMER SIDING SYSTEM

A look that lasts forever



NOVIPRO™ HAND-SPLIT SHAKE PANEL

FAST
and FIT

The rugged beauty of wood made timeless without the maintenance

NOVIK
INNOVATIVE POLYMERS



New Performance Features




- Replicates the look and feel of real hand-split shake cedar shingles with added performance and characteristics that will withstand the test of time.
- Made of injection molded copolymer for superior quality.
- Resists warping and impact at extreme temperature variations.
- Standard color-thru panel with U.V. stabilizer to prevent discoloration.
- Superior quality coating on blended colors.
- Accessories available in matching colors (ex. Corners, starter strips, J-channels).
- Products from different production runs can be mixed and matched.
- Easy to install.



No paint required-ever
Virtually maintenance-free



1 Nail locators that facilitate installation by indicating precise nail locations.



4 Superior interlocking system designed and tested to withstand hurricane windload.



4 Panels are held securely in place with extra long lock tabs that engage easily for faster and easier installation.

Dimensions
 (19" x 48" / 48,26 cm x 121,9 cm)
 9 panels / approx. 50 square feet per carton



NEW
Hand-Split Shake corner
 Adjustable at each row



NOVIPRO™ HAND-SPLIT SHAKE PANEL



The rugged beauty of wood made timeless without the maintenance

You can now recreate the old rustic charm of hand crafted traditional homes with the NOVIPRO™ Hand-Split Shake siding system.

Unlike real hand-split shakes that require expensive and time consuming maintenance, the NOVIPRO™ Hand-Split Shake siding system will not rot, split, shrink, absorb water or be destroyed by insects and will maintain its original look for years to come.

Testing performed

Test	Standard testing	Result for NOVIPRO™
Fire rating	In accordance with E84	Class C fire resistance
Impact	In accordance with ASTM3679	Pass
Accelerated U.V. exposure	In accordance with ASTM1435	Virtually no fading
Wind	In accordance with ASTM5206	> 160MPH

* Certified testing reports by independant laboratories



What is the Fast-Fit approach?
New features that simplify installation!

1 Centered nailing hole to secure the panel.

2 Angle that facilitates insertion.

3 Larger tabs on the back of the panel to facilitate insertion.

4 Special temperature lines molded to ensure precise installation.

Deep wood grain texture and nice shadow lines on all exposed surface for a natural wood appearance.

Back of panel





Widest selection of solid and blended colors on the market.



NOVIK
NOVIK
 INNOVATIVE POLYMERS

Phone: 418.878.6161 Toll-Free: 888.847.8057
 info@novik.com

www.novik.com

Actual colors may differ from the ones shown due to the printing process.
 Novik reserves the right to add or remove certain colors without notice.
 Check store samples.