


Data Sheet

Oak Harbor™ Series of Solid Vinyl Siding




Illustration	Description/Packaging	Colors/Color Nos.	* Premium Colors made with Armor Coat UVA™
--------------	-----------------------	-------------------	--



Double 4"
Length 12' 6"
24 Panels/Carton
2 Sq./Carton
Carton Weight: 84.80 lbs.

White Birch (02)	Summer Wheat (26)	*Adobe Clay (60)
Classic Sand (11)	Autumn Taupe (28)	*Terra Clay (69)
Warm Sandalwood (17)	Harbor Stone (44)	*Victorian Slate (67)
Sunny Maize (22)	*Concord Green (48)	*Charcoal Grey (84)
Providence Yellow (24)	*Vintage Sage (55)	


Illustration	Description/Packaging	Colors/Color Nos.	* Premium Colors made with Armor Coat UVA™
--------------	-----------------------	-------------------	--



Double 5"
Length 12'
20 Panels/Carton
2 Sq./Carton
Carton Weight: 77.90 lbs.

White Birch (02)	Autumn Taupe (28)	*Victorian Slate (67)
Classic Sand (11)	Harbor Stone (44)	*Charcoal Grey (84)
Warm Sandalwood (17)	*Vintage Sage (55)	
Sunny Maize (22)	*Adobe Clay (60)	
Summer Wheat (26)	*Terra Clay (69)	

Illustration	Description/Packaging	Colors/Color Nos.	* Premium Colors made with Armor Coat UVA™
--------------	-----------------------	-------------------	--



4.5" Dutchlap
Length 12' 1"
22 Panels/Carton
2 Sq./Carton
Carton Weight: 81.50 lbs.

White Birch (02)	Autumn Taupe (28)	*Victorian Slate (67)
Classic Sand (11)	Harbor Stone (44)	*Charcoal Grey (84)
Warm Sandalwood (17)	*Vintage Sage (55)	
Sunny Maize (22)	*Adobe Clay (60)	
Summer Wheat (26)	*Terra Clay (69)	

Illustration	Description/Packaging	Colors/Color Nos.	* Premium Colors made with Armor Coat UVA™
--------------	-----------------------	-------------------	--



5" Dutchlap
Length 12'
20 Panels/Carton
2 Sq./Carton
Carton Weight: 83.10 lbs.

White Birch (02)	Autumn Taupe (28)	*Victorian Slate (67)
Classic Sand (11)	Harbor Stone (44)	*Charcoal Grey (84)
Warm Sandalwood (17)	*Vintage Sage (55)	
Sunny Maize (22)	*Adobe Clay (60)	
Summer Wheat (26)	*Terra Clay (69)	

Oak Harbor Vinyl Siding w/Reinforced Nail Hem

Styles to fit your most exacting need.

Product Test Data

Siding Thickness.....	.042" ± .001"
Specific Gravity.....	1.45
Tensile Strength (PSI).....	7,154
Tensile Modulus (PSI).....	416,900
IZOD Impact Strength @ 32°F.....	Passes per ASTM D3679
Heat Deflection Temp. @ 264 PSI.....	169°F
Coefficient of Linear Expansion.....	3.30 x 10 ⁻⁵
Weight.....	.42 lbs. per square
Warpage.....	0.00"
Heat Shrinkage.....	0.3%



Style Crest, Inc.
2450 Enterprise Street
Drawer A
Fremont, OH 43420

Impact Resistance.....	Passes per ASTM D3679
Surface Distortion @ 140°F.....	0
Flame Spread Index.....	10
Fire Rating.....	Class A
Smoke Developed.....	.395
Fuel Contribution.....	0
Average Time Of Burning.....	Self extinguished
Average Extent Of Burning.....	2.379mm
Weathering.....	Passes per ASTM D3679
Windload Rating *.....	193 MPH

*(Wind Velocity based on IBC)

Oak Harbor™ Vinyl Siding passes or exceeds all industry standards per ASTM D3679.

Made in the U.S.A. by America's dedicated workforce.
Specifications subject to change without notice.



Sponsored by the Vinyl Siding Institute
Consult the VSI web site at www.vinylsiding.org
for a current list of certified products and colors.
Oak Harbor Data 05/04/07