



## Thermo-Vyne® Series Double Hung Vinyl Replacement Window

### Features

- **Block & Tackle Balances** ensuring a smooth and quiet operation
- **Double Fin Seal Weather Stripping** at all sash perimeters
- **Positive Inter-lock at meeting rail** guarantee a superior fit
- **Sloped sill system** for superior water drainage
- **Extruded aluminum locking half screen** for added security
- **Multi-chambered extrusion with .060" wall thickness** for strength and insulating value
- **Tilt in top and bottom sash** designed for easy cleaning
- **Exterior Glazed Sashes** provides exceptional interior & curb appeal.
- **Metal-free warm edge Duralite® Spacer** ensures minimal heat transfer resulting in warm inside glass
- **Grills between glass** offers easy cleaning and aesthetic appeal
- **13/16" Insulated Glass** substantially reduces home heating and cooling costs
- **Mechanically fastened corners** providing excellent performance and strength at an economical price
- **Excellent Performance Ratings...**
  - (Double Hung Values)
  - SHGC - .30
  - U-Value - .30
  - Air infiltration - .28 cfm/sqft
  - Structural test – DP -35

### Options

|  |  |
|--|--|
| <b>Grids –</b> <ul style="list-style-type: none"> <li>• Flat</li> <li>• Contour</li> <li>• SDL</li> <li>• Stain Glass</li> </ul> | <b>Optional Painted Exterior</b> <ul style="list-style-type: none"> <li>• Tan, Brown, White</li> </ul> |
| <b>Glass</b> <ul style="list-style-type: none"> <li>• Optional low-E coatings</li> <li>• Optional Argon Fill</li> </ul>          |  |
| <b>Screens</b> <ul style="list-style-type: none"> <li>• Full Screen</li> </ul>   |  |

Mercury Excelum, Inc.

860.292.1800

[www.mercurvexcelum.com](http://www.mercurvexcelum.com)

[marketing@mercurvexcelum.com](mailto:marketing@mercurvexcelum.com)